POTORQUE POWER TONG & TUBULAR RUNNING SERVICES

Proper power tong selection for every casing connection is a critical aspect of any tubular running operation. Premium connection torques may dictate the use of specialty components such as hydraulic / air slips, or integral back-ups for your power tong. Depending on manufacturers specifications integral back-ups may be a make-up requirement. Our expansive fleet of specialized TRS equipment is available to support the make-up of high torque connection values up to 50,000 ft/lbs. We are able to do this while still maintaining the smallest possible foot print on the rig floor. Our focus is having the right TRS equipment specific to every job.

TOTAL RIG SOLUTIONS™

Stay

7.5/8

CANADA 780.933.0404 UNITED STATES 713.300.5216

PROTORQUETECH.COM

CONVENTIONAL & INTEGRAL POWER TONGS

PROTORQUE POWER TONG & TUBULAR RUNNING SERVICES



TECHNICIANS

- Our experienced and skilled power tong technicians play a major role in the safety and efficiency of a casing run. This makes the selection of your power tong service company a key component of overall performance.
- ProTorque attracts and employs some of the industries most talented and experienced casing running technicians. Every detail of a casing run must be considered when looking for cost savings and efficiency; particularly on long production strings where every second counts while maintaining a safe operation. When making-up hundreds of connections, filling on the fly and selecting the correct handling equipment (air or hydraulic powered slips); we save time and effort on long challenging casing runs. ProTorque can meet handling requirements of up to 500 ton of hoist capability.

	STANGER OF REPORT OF SOM	그 아파는 것 같아요. 그는 것 같아요. 그는 것이 가지 않았다. 영화가 가지 않는 것이 같아요.
CANADA	FEATURES:	Conventional tong range: 2.63 - 20" (66.8 - 508 mm)
		Integral power tong range: 2.63 - 13.63" (66.8 - 346.2 mm)
CANADA 780.933.0404		Torque Output: up to 50,000 ft/lbs (67,790 Nm)
UNITED STATES 713.300.5216 Protorquetech.com		Wrap around (low penetrating) dies available for most sizes and tongs, upon request
		Handling equipment: 500 ton capability within North America
		High Torque Strap Tongs: 50,000 ft/lbs (67,790 Nm)
		Hydraulic / Air Slips: 200 & 350 ton available